

CITY-FITNES

C-SPORT | ALIVIO 2X9SP | YSB55



THE IMAGE SHOWN IS INDICATIVE ONLY. Components and graphic details may differ from the actual model.

COLOR	TBD	CASSETTE / FREEWHEEL	Shimano, CS-HG200-9
FRAME	C-SPORT alu disc frame, 700C OLD 135mm, No Pivot, DISC version, integrated cable routing, SMOOTH WELDING, 1"1/8 aheadset, Seat tube 31.6mm, SIZE:43cm/47cm/51cm/55cm/59cm	BRAKE	Shimano Altus, Disc Brake Assembled Set, BL-MT200(L), BR-MT200(F), Black, For Post Mount, Resin Pad, 750mm(43/47/51CM), 800mm(55/59CM)
SEATPOST CLAMP	MX-112C 34.9mm alloy AN Black (14.4gr)	BRAKE LEVER	Shimano Included in the brake set
HEADSET	FSA NO.8B/ZS4D 1-1/8" SEMI-INTEGRATED LOWER PART + INTEGRATED UPPER PART, W/H2166B 15MM TOP COVER FOR TAPERED 46MM/50MM OD HEAD TUBE	FRONT HUB	Formula CL-1420 Center lock, 32hole, 14G, O.L.D. 100mm AXEL 108mm with QR22
FORK	FF28"AL DISC118, ALU FORK 28" 700c, 1-1/8" Alloy steerer, alu blades, integrated 50mm, offset 45mm, Postmount disc brake version, 700x40c max tire size	REAR HUB	Formula CL-1422 Center lock, 32hole, 14G, O.L.D. 135mm AXEL145mm, for Shimano 8/9/10speed with QR22
SHIFTER	Shimano, SL-M3100-2L, Alivio, Left, 2-Speed Rapidfire Plus Mono, 1800mm Inner, W/O Optical Gear Display	RIM/WHEELSET	Velomann disc version, alloy, 700c 622x19 32H, pair spoke 2x16 (500g), pin joint, tubeless ready, EN standard
REAR DERAILLEUR	Shimano, RD-T4000-SGS, Alivio, 9-Speed, Top-Normal, Direct Attachment	TIRE	Kenda K1067 - Kwick Tendril , 700x38c, TPI60, black color + Kshield 3mm antipunctures
FRONT DERAILLEUR	Shimano, FD-T3000-2-TS3, Acera, for 2x9, Top-Swing, Dual-Pull, 34.9mm Band, CS-Angle:63-68, For Top Gear:46T, CL:48.8mm	STEM	Velomann 3D forged 6061 Alloy, 12° 31,8mm 28,6mm, SB black and ED black bolts, size: 70mm-43cm, 100mm-47cm/51cm, 120mm-55cm/59cm
CRANKSET	Shimano, FC-MT210-2, For Rear 9-Speed, 2-Pcs FC, 170mm and 175mm, 46-30T W/CG, W/BB Parts (BSA), crank lenght: 170mm(43-47CM) / 175mm(51-55-59CM)	HANDLEBAR	Velomann Alloy 6061 DB, 620mm, flat bar, 9° bend, 31,8mm
BOTTOM BRACKET	Included in the crankset	GRIP / TAPE	Velo Ergonomic Double density VLG-1824-D2 kraton Bianchi color Celeste / Gel Black 131,6mm closed end
CHAIN	KMC Z-99 1/2"X11/128"X114LINKS, FOR 9-SPEED	SEATPOST	Velomann Alloy shaft AL6061, alloy head, 15mm offset, 31,6mm
		SADDLE	Velomann, 269mm x 146mm, 285gr, steel rail, black-ck semi PU cover 7823#
		PEDALS	VP VPE-899 One piece PP body, TPE tread axle 7mm boron steel EPB system size 111x84mm with reflector

C-SPORT | ACERA 24SP | YSBD3



THE IMAGE SHOWN IS INDICATIVE ONLY. Components and graphic details may differ from the actual model.

COLOR	TBD	CASSETTE / FREEWHEEL	Shimano, CS-HG200-8, 8-Speed, 12-14-16-18-21-24-28-32
FRAME	C-SPORT alu disc frame, 700C OLD 135mm, No Pivot, DISC version, integrated cable routing, SMOOTH WELDING, 1.1/8 aheadset, Seat tube 31.6mm, SIZE:43cm/47cm/51cm/55cm/59cm	BRAKE	Shimano INCLUDED IN L/SHIFTER
SEATPOST CLAMP	MX-112C 34.9mm alloy AN Black (14.4gr)	BRAKE LEVER	Shimano ùIncluded in the brake set
HEADSET	FSA NO.8B/ZS4D 1-1/8" SEMI-INTEGRATED LOWER PART + INTEGRATED UPPER PART, W/H2166B 15MM TOP COVER FOR TAPERED 46MM/50MM OD HEAD TUBE	FRONT HUB	Formula CL-1420 Center lock, 32hole, 14G, O.L.D. 100mm AXEL 108mm with QR22
FORK	FF28"AL DISC118, ALU FORK 28" 700c, 1.1/8" Alloy steerer, alu blades, integrated 50mm, offset 45mm, Postmount disc brake version, 700x40c max tire size	REAR HUB	Formula CL-1422 Center lock, 32hole, 14G, O.L.D. 135mm AXEL145mm, for Shimano 8/9/10speed with QR22
SHIFTER	Shimano Disc Brake Assembled Set, ST-EF505(L), BR-MT200(F), W/O ADAPTER, RESIN PAD, 750MM HOSE	RIM/WHEELSET	Velomann disc version, alloy, 700c 622x19 32H, pair spoke 2x16 (500g), pin joint, tubeless ready, EN standard
REAR DERAILLEUR	Shimano , RD-M3020-8, ACERA, SGS 7/8-SPEED, DIRECT ATTACHMENT	TIRE	Kenda K1067 - Kwick Tendril , 700x38c ,TPI60
FRONT DERAILLEUR	Shimano FD-TY600-L3, TOURNEY, FOR 3X6/7/8, TOP-SWING, DUAL-PULL, BAND TYPE, CS-ANGLE:63-66, FOR 42T, CL:47.5/50MM	STEM	Velomann 3D forged 6061 Alloy, 12° 31,8mm 28,6mm, SB black and ED black bolts, 70mm x size 43cm - 100mm x size 47cm/51cm -120mm x size 55cm/59cm
CRANKSET	Shimano, FC-TY301, For Rear 6/7/8-Speed, 42x34x24T W/CG, Chain Case Compatible, Black, Bulk 170mm/ 175mm	HANDLEBAR	Velomann Alloy 6061 DB, 620mm, flat bar, 9° bend, 31,8mm
BOTTOM BRACKET	Shimano, BB-UN101, Spindle:Square Type, Shell:BSA 68mm,Spindle:122.5mm(D-NL), W/Fixing Bolt	GRIP / TAPE	Velo Ergonomic Double density VLG-1824-D2 kraton Bianchi color Celeste / Gel Black 131,6mm closed end
CHAIN	KMC Z-8.1 1/2"x3/32"x116L, FOR 8-SPEED	SEATPOST	Velomann Alloy shaft AL6061, alloy head, 15mm offset, 31,6mm
		SADDLE	Velomann, 269mm x 146mm, 285gr, steel rail, black-ck semi PU cover
		PEDALS	FDP VPE-899 One piece PP body, TPE tread axle 7mm boron steel EPB system size 111x84mm with reflector

C-SPORT STEP THROUGH | ACERA 24SP | YSBD9



THE IMAGE SHOWN IS INDICATIVE ONLY. Components and graphic details may differ from the actual model.

COLOR	TBD	CASSETTE / FREEWHEEL	Shimano, CS-HG200-8, 8-Speed, 12-14-16-18-21-24-28-32
FRAME	C-SPORT Step Through alu disc frame, 700C OLD 135mm, No Pivot, DISC version, integrated cable routing, SMOOTH WELDING, 1.1/8 aheadset, Seat tube 31.6mm, SIZE:43cm/47cm/51cm/55cm	BRAKE	Shimano INCLUDED IN L/SHIFTER
SEATPOST CLAMP	MX-112C 34.9mm alloy AN Black (14.4gr)	BRAKE LEVER	Shimano ùIncluded in the brake set
HEADSET	FSA NO.8B/ZS4D 1-1/8" SEMI-INTEGRATED LOWER PART + INTEGRATED UPPER PART, W/H2166B 15MM TOP COVER FOR TAPERED 46MM/50MM OD HEAD TUBE	FRONT HUB	Formula CL-1420 Center lock, 32hole, 14G, O.L.D. 100mm AXEL 108mm with QR22
FORK	FF28" AL DISC118, ALU FORK 28" 700c, 1.1/8" Alloy steerer, alu blades, integrated 50mm, offset 45mm, Postmount disc brake version, 700x40c max tire size	REAR HUB	Formula CL-1422 Center lock, 32hole, 14G, O.L.D. 135mm AXEL145mm, for Shimano 8/9/10speed with QR22
SHIFTER	Shimano Disc Brake Assembled Set, ST-EF505(L), BR-MT200(F), W/O ADAPTER, RESIN PAD, 750MM HOSE	RIM/WHEELSET	Velomann disc version, alloy, 700c 622x19 32H, pair spoke 2x16 (500g), pin joint, tubeless ready, EN standard
REAR DERAILLEUR	Shimano, RD-M3020-8, ACERA, SGS 7/8-SPEED, DIRECT ATTACHMENT	TIRE	Kenda K1067 - Kwick Tendril, 700x38c, TPI60
FRONT DERAILLEUR	Shimano FD-TY600-L3, TOURNEY, FOR 3X6/7/8, TOP-SWING, DUAL-PULL, BAND TYPE, CS-ANGLE:63-66, FOR 42T, CL:47.5/50MM	STEM	Velomann 3D forged 6061 Alloy, 12° 31,8mm 28,6mm, SB black and ED black bolts, 70mm x size 43cm - 100mm x size 47cm/51cm -120mm x size 55cm/59cm
CRANKSET	Shimano, FC-TY301, For Rear 6/7/8-Speed, 42x34x24T W/CG, Chain Case Compatible, Black, Bulk 170mm/ 175mm	HANDLEBAR	Velomann Alloy 6061 DB, 620mm, flat bar, 9° bend, 31,8mm
BOTTOM BRACKET	Shimano, BB-UN101, Spindle:Square Type, Shell:BSA 68mm, Spindle:122.5mm(D-NL), W/Fixing Bolt	GRIP / TAPE	Velo Ergonomic Double density VLG-1824-D2 kraton Bianchi color Celeste / Gel Black 131,6mm closed end
CHAIN	KMC Z-8.1 1/2"x3/32"x116L, FOR 8-SPEED	SEATPOST	Velomann Alloy shaft AL6061, alloy head, 15mm offset, 31,6mm
		SADDLE	Velomann, 269mm x 146mm, 285gr, steel rail, black-ck semi PU cover
		PEDALS	FDP VPE-899 One piece PP body, TPE tread axle 7mm boron steel EPB system size 111x84mm with reflector

C-SPORT CROSS | ACERA 24SP | YSBB2



THE IMAGE SHOWN IS INDICATIVE ONLY. Components and graphic details may differ from the actual model.

COLOR	TBD	CASSETTE / FREEWHEEL	Shimano, CS-HG200-8, 8-Speed, 12-14-16-18-21-24-28-32
FRAME	C-SPORT CROSS alu disc frame,700C OLD 135mm, No Pivot, DISC version, integrated cable routing, SMOOTH WELDING, 1.1/8 semintegrated Aheadset. Seat tube 31.6mm, SIZE:43cm/47cm/51cm/55cm	BRAKE	Shimano INCLUDED IN L/SHIFTER
SEATPOST CLAMP	MX-112C 34.9mm alloy AN Black (14.4gr)	BRAKE LEVER	Shimano Included in the brake set
HEADSET	FSA NO.8B/ZS4D 1-1/8" SEMI-INTEGRATED LOWER PART + INTEGRATED UPPER PART, W/H2166B 15MM TOP COVER FOR TAPERED 46MM/50MM OD HEAD TUBE	FRONT HUB	Formula CL-1420 Center lock, 32hole, 14G, O.L.D. 100mm AXEL 108mm with QR22
FORK	Suntour SF16-NEX-HLO-DS-700C, 1.1/8" STEEL THREADLESS STEERER , STEEL CP STANCHION,ALLOY BLADES, DISC VERSION, FOR 700C W/SR SUNTOUR DECAL, 63MM TRAVEL, HYDRAULIC LOCK, POSTMOUNT	REAR HUB	Formula CL-1422 Center lock, 32hole, 14G, O.L.D. 135mm AXEL145mm, for Shimano 8/9/10speed with QR22
SHIFTER	Shimano Disc Brake Assembled Set, ST-EF505(L), BR-MT200(F), W/O ADAPTER, RESIN PAD, 750MM HOSE	RIM/WHEELSET	Velomann disc version, alloy, 700c 622x19 32H, pair spoke 2x16 (500g), pin joint, tubeless ready, EN standard
REAR DERAILLEUR	Shimano , RD-M3020-8, ACERA, SGS 7/8-SPEED, DIRECT ATTACHMENT	TIRE	Kenda 700x40,
FRONT DERAILLEUR	Shimano FD-TY600-L3, TOURNEY, FOR 3X6/7/8, TOP-SWING, DUAL-PULL, BAND TYPE, CS-ANGLE:63-66, FOR 42T, CL:47.5/50MM	STEM	Velomann 3D forged 6061 Alloy, 12° 31,8mm 28,6mm, SB black and ED black bolts, size: 70mm-43cm, 100mm-47cm/51cm, 120mm-55cm/59cm
CRANKSET	Shimano, FC-TY301, For Rear 6/7/8-Speed, 42x34x24T W/CG, Chain Case Compatible, Black, Bulk 170mm/ 175mm	HANDLEBAR	Velomann Alloy 6061 DB, 620mm, flat bar, 9° bend, 31,8mm
BOTTOM BRACKET	Shimano, BB-UN101, Spindle:Square Type, Shell:BSA 68mm,Spindle:122.5mm(D-NL), W/Fixing Bolt	GRIP / TAPE	Velo Ergonomic Double density VLG-1824-D2 kraton Bianchi color Celeste / Gel Black 131,6mm closed end
CHAIN	KMC Z-72 1/2"x3/32"x116L, FOR 8-SPEED	SEATPOST	Velomann Alloy shaft AL6061, alloy head, 15mm offset, 31,6mm
		SADDLE	Velomann, 269mm x 146mm, 285gr, steel rail, black-ck semi PU cover 7823#
		PEDALS	VP VPE-899 One piece PP body, TPE tread axle 7mm boron steel EPB system size 111x84mm with reflector

C-SPORT CROSS STEP THROUGH | ACERA 24SP | YSBB3



THE IMAGE SHOWN IS INDICATIVE ONLY. Components and graphic details may differ from the actual model.

COLOR	TBD
FRAME	C-SPORT CROSS Step Through alu disc frame, 700C OLD 135mm, No Pivot, DISC version, integrated cable routing, SMOOTH WELDING, 1.1/8 semintegrated Aheadset. Seat tube 31.6mm, SIZE:43cm/47cm/51cm
SEATPOST CLAMP	MX-112C 34.9mm alloy AN Black (14.4gr)
HEADSET	FSA NO.8B/ZS4D 1-1/8" SEMI-INTEGRATED LOWER PART + INTEGRATED UPPER PART, W/H2166B 15MM TOP COVER FOR TAPERED 46MM/50MM OD HEAD TUBE
FORK	Suntour SF16-NEX-HLO-DS-700C, 1.1/8" STEEL THREADLESS STEERER , STEEL CP STANCHION,ALLOY BLADES, DISC VERSION, FOR 700C W/SR SUNTOUR DECAL, 63MM TRAVEL, HYDRAULIC LOCK, POSTMOUNT
SHIFTER	Shimano Disc Brake Assembled Set, STEF505(L), BR-MT200(F), W/O ADAPTER, RESIN PAD, 750MM HOSE
REAR DERAILLEUR	Shimano , RD-M3020-8, ACERA, SGS 7/8-SPEED, DIRECT ATTACHMENT
FRONT DERAILLEUR	Shimano FD-TY600-L3, TOURNEY, FOR 3X6/7/8, TOP-SWING, DUAL-PULL, BAND TYPE, CS-ANGLE:63-66, FOR 42T, CL:47.5/50MM
CRANKSET	Shimano, FC-TY301, For Rear 6/7/8-Speed, 42x34x24T W/CG, Chain Case Compatible, Black, Bulk 170mm/ 175mm
BOTTOM BRACKET	Shimano, BB-UN101, Spindle:Square Type, Shell:BSA 68mm,Spindle:122.5mm(D-NL), W/Fixing Bolt
CHAIN	KMC Z-72 1/2"x3/32"x116L, FOR 8-SPEED

CASSETTE / FREEWHEEL	Shimano, CS-HG200-8, 8-Speed, 12-14-16-18-21-24-28-32
BRAKE	Shimano INCLUDED IN L/SHIFTER
BRAKE LEVER	Shimano Included in the brake set
FRONT HUB	Formula CL-1420 Center lock, 32hole, 14G, O.L.D. 100mm AXEL 108mm with QR22
REAR HUB	Formula CL-1422 Center lock, 32hole, 14G, O.L.D. 135mm AXEL145mm, for Shimano 8/9/10speed with QR22
RIM/WHEELSET	Velomann disc version, alloy, 700c 622x19 32H, pair spoke 2x16 (500g), pin joint, tubeless ready, EN standard
TIRE	Kenda 700x40
STEM	Velomann 3D forged 6061 Alloy, 12° 31,8mm 28,6mm, SB black and ED black bolts, size: 70mm-43cm, 100mm-47cm/51cm, 120mm-55cm/59cm
HANDLEBAR	Velomann Alloy 6061 DB, 620mm, flat bar, 9° bend, 31,8mm
GRIP / TAPE	Velo Ergonomic Double density VLG-1824-D2 kraton Bianchi color Celeste / Gel Black 131,6mm closed end
SEATPOST	Velomann Alloy shaft AL6061, alloy head, 15mm offset, 31,6mm
SADDLE	Velomann, 269mm x 146mm, 285gr, steel rail, black-ck semi PU cover 7823#
PEDALS	VP VPE-899 One piece PP body, TPE tread axle 7mm boron steel EPB system size 111x84mm with reflector